

YOUR ACCESS KEY TO SUSTAINABILITY



PRYMER FAST 500

FAST DRYING ODORLESS POLYURETHANE PRIMER FOR SUBFLOORS PREPARATION



Choose Chimiver, together for a sustainable future

PRODUCTS CERTIFICATION







GREEN BUILDING PROTOCOLS

BUILDING C	V4	CATEGORY CREDIT	INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS	UP TO 3 POINTS
DE ED DE SERVICE DE LA COMPANSION DE LA	V4.1	CATEGORY CREDITS	INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS	UP TO 3 POINTS
BREEAM®	INTERNATIONAL NEW CONSTRUCTION RFO	CREDITS	HEA 02 INDOOR AIR QUALITY	/
WELL BUILDING WELL BUILDING	V2	CONCEPT	MATERIALS	/
		FEATURES	X06 VOC RESTRICTIONS	UP TO 4 POINTS

MINIMAL AMBIENTALS REQUIREMENTS



2.5.13 b) They do not contain any Cadmium additives, Lead, Hexavalent Chromium, Mercury, Arsenic or Selenium



Documento redatto in collaborazione con









LEED Proven Provider per i protocolli LEED v4ID+Ce BD+C



LEED Fellow LEED Green Associate





12 LEED ® APBD+C



2 LEED ® APID+C



2 LEED ® APO+M





3 BREEAM * ASSESSOR NC 2 BREEAM * ASSESSOR INFO 2 BREEAM * ASSESSOR IN USE 2 BREEAM * AP





OTHER DATA

RELATIVE DENSITY:	1,16 KG/Lt
VOC	0,00%



PACKAGING COMPOSITION							
LABEL	S	PP	Q	-			
TANK	MATERIALS	HD-PE	% RECYCLED	-			
САР	2	PP		-			

